

SLS40-A

Laser Scintillometer for Towers – with Beam Steering



Photo courtesy of CSIR, South Africa

The Scintec SLS40-A Scintillometer measures turbulence, heat flux and momentum flux by purely optical means. In combination with other meteorological sensors the system can determine latent heat flux or evaporation.

The SLS40-A has both built-in automatic beam steering and vibration correction. It is designed for operation on towers or other platforms which are prone to vibration or long-term-drift. Vibration effects are compensated by using the signal of four instead of two optical detectors.

Each SLS Series Scintillometer consists of a laser transmitter pointing at a receiver. Temperature fluctuations in the air cause variations of the light

intensity captured at the receiver. The scintillometer evaluates such variations to yield turbulence information.

The line averaging over the optical path results in spatially representative data and outstanding temporal resolution – a critical edge over data collected from conventional point sensors. The scintillometer provides high sensitivity and accuracy – without mechanical flow distortion or any moving part.

The proprietary displaced-beam technique of the SLS Series Scintillometers opens up access to mechanical turbulence quantities (momentum flux, kinetic-energy dissipation rate) without need to feed in any external wind data.

FEATURES

- heat flux, momentum flux by purely optical means
- suitable for stable and unstable conditions
- measures C_n^2 , C_T^2 , l_0
- crosswind option available
- spatially averaging technique
- high temporal resolution
- low statistical noise
- no flow distortion
- easy installation and operation
- included Signal Processing Unit performs all calculations

APPLICATIONS

- turbulence studies
- air quality and atmospheric dispersion
- spatially-averaged wind measurements
- optical propagation conditions
- military
- surface energy balance
- evapotranspiration monitoring
- agrometeorology, forestry
- satellite data ground truth

SLS40-A

Data output

Data output includes (but is not limited to):

- structure parameter of refractive index fluctuations (C_n^2)
- inner scale of refractive index fluctuations (ℓ_0)
- structure parameter of temperature fluctuations (C_T^2)
- dissipation rate of turbulent kinetic energy
- sensible heat flux
- momentum flux
- Obukhov length
- path-averaged wind speed perpendicular to the beam axis (with crosswind extension)
- mean, standard deviation, minimum and maximum of intensity
- correlation coefficient of intensity
- data quality code

Description	Specifications			Remarks
Optical wavelength	670 nm			visible (red)
Mean output power	1 mW			laser safety class 2M (IIIa)
Beam divergence	3 x 8 mrad			
Beam-steering scan cone diameter	1 degree			
Path length	50 - 250 m			others optional
Analogue input channels	input range 0 - 10 V			11 optional channels, 12 bit resolution
Supply voltage and current	12 V, 1.5 A			for transmitter, receiver, SPU
	12 V, 0.2 A			for window heating
Operating temperature	-20 to +50 °C			
Dimensions	70 x 11 x 11 cm / 62 x 12 x 12 cm			transmitter / receiver
Weights	3.5 kg / 4.1 kg			transmitter / receiver
Measurement ranges ⁽¹⁾	from	to	unit	Depends on
Structure constant C_n^2	1×10^{-16}	3×10^{-12}	$m^{-2/3}$	path length
Inner scale ℓ_0	2	16	mm	path length
Structure constant C_T^2	1×10^{-4}	3	$K^2 m^{-2/3}$	path length ⁽²⁾
Kinetic-energy dissipation rate ϵ	2×10^{-4}	1	$m^2 s^{-3}$	path length ⁽²⁾
Sensible heat flux	2 -2	600 -120	$W m^{-2}$ $W m^{-2}$	path length and height, Obukhov length ⁽²⁾
Momentum flux	-4×10^{-3}	-1.2	$N m^{-2}$	path length and height, Obukhov length ⁽²⁾
Wind speed	0.01	10	$m s^{-1}$	(with Crosswind Extension)

¹⁾ Typical values for path 100 m long and 2 m high; ²⁾ Values for normal temperature and pressure

Scintec AG

Willhelm-Maybach-Str. 14
D-72108 Rottenburg
Germany

Tel. [+49] 74 72 9 86 43 0
Fax [+49] 74 72 9 80 87 14
info@scintec.com

Scintec Corporation

5950 Shiloh Road East
Atlanta/Alpharetta, GA 30005
U.S.A.

Tel. [+1] (770) 887 - 0557
Tel. [+1] (770) 887 - 7849
sales@scintec.com

www.scintec.com

Specifications are subject to change without notice.
Patents: US 5,303,024; DE 4113 308

Scintec 